

UVC-G5-PTZ-B

SKU 011128 · UVC-G5-PTZ



MARCA · UBIQUITI

UVC-G5-PTZ

Compact, all-weather camera with ultra-low latency pan-tilt-zoom control and versatile mounting options.

ESPECIFICACIONES TÉCNICAS

RESUMEN

Dimensiones	Without mount: Ø90 x 152.5 mm , (Ø3.5 x 6"), , With mount: 90 x 94 x 179.5 mm , (3.5 x 3.7 x 7")
Visión nocturna IR	20 m (65 ft)
Zoom Mode	2x Optical
Detección inteligente (personas, vehículos, animales)	Sí
Resolución	2K
Campo de visión	Wide: H: 99.7°, V: 51.9°, D: 121°, Tele: H: 45.5°, V: 25.4°, D: 52.4°
Pan-Tilt Range	Pan: 350°, Tilt: 100°
Audio	Microphone
Resistencia a intemperie	IP66
Resistencia a manipulación	IK04
Montaje	Pared, pole mount (incluido), Conduit adapter, surface, in-ceiling, pendant, corner mount (opcional)

RENDIMIENTO

Interfaz de red	10/100 MbE RJ45 port
VIDEO	
Cuadros por segundo (máx.)	30 FPS
Resolución	4MP 2688 x 1512 (16:9)
ÓPTICA	
Sensor	5MP 1/2.7" CMOS
Lente	F 3.42–6.85 mm; f/1.85–f/2.4
Modo nocturno	Built-in IR & white LED illumination with IR cut filter

HARDWARE

Consumo máximo	14W
Rango de voltaje	37–57V DC
Método de alimentación	PoE+
Pole Mount Diameter	1.5–2" (38–50 mm)
Peso	Without mount: 580 g (1.3 lb), With mount: 650 g (1.4 lb)
Material de carcasa	Aluminum alloy, polycarbonate
Material de montaje	Pared: polycarbonate, Pole mount: aluminum alloy
Botón	(1) Factory reset
Temperatura de operación	-30 to 45° C (-22 to 113° F)
Humedad de operación	0 to 90%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC