

LAP-120

SKU 020268 · LAP-120



MARCA · UBIQUITI

LAP-120

Ultra-lightweight, 5 GHz access point with a versatile, ball-joint mount.

ESPECIFICACIONES TÉCNICAS

MECÁNICA

Dimensiones	452.3 x 78.7 x 54.4 mm, (17.8 x 3.1 x 2.14")
Peso	420 g (14.82 oz)
Wind Loading	77 N at 200 km/h (17.3 lbf at 125 mph)
Wind Survivability	200 km/h (125 mph)

HARDWARE

Interfaz de red	(1) GbE RJ45 port
Método de alimentación	Passive PoE 2-pair (4, 5+; 7, 8 return)
Fuente de poder	24V, 0.5A gigabit PoE adapter (incluido)
Rango de voltaje	20—27V DC
Consumo máximo	8W
Temperatura de operación	-40 to 70° C (-40 to 158° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Shock and Vibration Certification	ETSI300-019-1.4
Certificaciones	CE, FCC, IC

SOFTWARE

Operating Modes	Access Point, Station
-----------------	-----------------------

FUNCIONES UBIQUITI ESPECÍFICAS

airMAX AC Mode	Sí
Discovery Protocol	Sí
Frequency Band Offset	Sí
Traffic Shaping with Burst Support	Sí
30/50/60 MHz Channels	Sí

SERVICIOS

Bridging	Sí
DHCP	Sí
Ping Watchdog	Sí
Routing	Sí
SNMP	Sí
SSH	Sí
Webserver	Sí

AJUSTE DE DISTANCIA

Ackless Mode	Sí
Dynamic Ack	Sí
QoS	WMM packet classification with user-level priority: High, Medium, Low

REPORTES ESTADÍSTICOS

Data Rates	Sí
Ethernet Link Rate	Sí
Packet Errors	Sí
Up Time	Sí
Wireless Distance	Sí

SISTEMA

Ganancia de antena	16 dBi
--------------------	--------