

## RP-5AC-Gen2

SKU 020821 · RP-5AC-Gen2



MARCA · UBIQUITI

## RP-5AC-Gen2

High-performance 5 GHz basestation for PtMP or PtP links. Provides up to 500+ Mbps data throughput.

## ESPECIFICACIONES TÉCNICAS

## MECÁNICA

Dimensiones	88 x 40 x 230 mm, (3.5 x 1.6 x 9.1")
Peso	400 g (14.1 oz)
Enclosure Materials	Die-cast aluminum
Wind Loading	342.5 N at 200 km/h (77 lbf at 125 mph)

## HARDWARE

Interfaz de red	(1) GbE RJ45 port
Método de alimentación	Passive PoE 2-pair (4, 5+; 7, 8 return)
Fuente de poder	24V, 1A gigabit PoE adapter (incluido)
Rango de voltaje	18–27V DC
Consumo máximo	9.5W
GPS	Sí
RF Connections	(2) RP-SMA (Waterproof), (1) GPS (Waterproof)

## LEDS

Signal Strength	Sí
Power	Sí
LAN	Sí
GPS	Sí
Temperatura de operación	-40 to 80° C (-40 to 176° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Shock and Vibration Certification	ETSI300-019-1.4
Certificaciones	CE, FCC, IC, RoHS, Anatel: 02137-18-08356

## SOFTWARE

Operating Modes	Access Point, Station
-----------------	-----------------------

## FUNCIONES UBIQUITI ESPECÍFICAS

airMAX AC Mode	Sí
Discovery Protocol	Sí
Frequency Band Offset	Sí
Traffic Shaping with Burst Support	Sí
30/50/60 MHz Channels	Sí

## SERVICIOS

Bridging	Sí
DHCP	Sí
Ping Watchdog	Sí
Routing	Sí
SNMP	Sí
SSH	Sí
Webserver	Sí

## AJUSTE DE DISTANCIA

Ackless Mode	Sí
Dynamic Ack	Sí
QoS	WMM packet classification with user-level priority: High, Medium, Low

## REPORTES ESTADÍSTICOS

Data Rates	Sí
Ethernet Link Rate	Sí
Packet Errors	Sí
Up Time	Sí
Wireless Distance	Sí

## SISTEMA