

## ETH-SP-G2

SKU 020911 · ETH-SP-G2



MARCA · UBIQUITI

## ETH-SP-G2

ESD protection for outdoor high-speed networks.

## ESPECIFICACIONES TÉCNICAS

## MECÁNICA

|                          |                                      |
|--------------------------|--------------------------------------|
| Dimensiones              | 91 x 61 x 32.5 mm (3.6 x 2.4 x 1.3") |
| Peso                     | 80 g (2.8 oz)                        |
| Material de carcasa      | Polycarbonate                        |
| Resistencia a intemperie | IPX5                                 |

## HARDWARE

|                                   |  |
|-----------------------------------|--|
| Interfaz de red                   | (2) RJ45 female connectors   |
| DC Spark-Over Voltage             | 90V @ 100V/s   |
| Max. Impulse Spark-Over Voltage   | 700V @ 1kV/μs  |
| Discharge Current                 | 10kA+  |
| Insulation                        | Max. Resistance: 1G ohm @ 50V  |
| Max. Capacitance                  | 1.0 pF @ 1 MHz   |
| Data Line Protection              | Up to 2.5 Gbps   |
| PoE Support                       | Sí   |
| ESD Protection                    | Absorbing transient current with response to surge voltage from 100V/s to 1kV/μs |
| Temperatura de operación          | -30 to 65° C (-22 to 149° F)   |
| Humedad de operación              | 10 to 90%, no condensada   |
| Shock and Vibration Certification | ETSI300-019-1.4 Standard   |