

## NS-5AC

SKU 020915 · NS-5AC



MARCA · UBIQUITI

## NS-5AC

UISP-supported WiFi radio designed for point-to-point and customer premises applications.

## ESPECIFICACIONES TÉCNICAS

## MECÁNICA

Dimensiones	With Mount:, 257 x 84 x 41 mm (10.1 x 3.3 x 1.6"), Without Mount:, 257 x 84 x 30 mm (10.1 x 3.3 x 1.2")
Peso	233 g (8.2 oz)
Enclosure Materials	UV-resistant polycarbonate
Montaje	Pole and Wall Mount (Mounts Incluido)

## HARDWARE

Interfaz de red	(2) GbE RJ45 ports
Método de alimentación	Passive PoE 2-pair (4, 5+; 7, 8 return), PoE alternative A (pairs 1, 2+; 3, 6 return)
Fuente de poder	24V, 0.5A gigabit PoE adapter (incluido)
Rango de voltaje	44-54V DC, 22-27V DC
Consumo máximo	9W

## LEDS

Signal Strength	Sí
Power	Sí
Ethernet	Sí
Temperatura de operación	-40 to 70° C (-40 to 158° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC, Anatel: 09603-19-08356

## SOFTWARE

Operating Modes	Access Point, Station
FUNCIONES UBIQUITI ESPECÍFICAS	
airMAX AC Mode	Sí
Discovery Protocol	Sí
Frequency Band Offset	Sí
Traffic Shaping with Burst Support	Sí
30/50/60 MHz Channels	Sí

## SERVICIOS

Bridging	Sí
DHCP	Sí
Ping Watchdog	Sí
Routing	Sí
SNMP	Sí
SSH	Sí
Webserver	Sí

## AJUSTE DE DISTANCIA

Dynamic Ack	Sí
QoS	WMM packet classification with user-level priority: High, Medium, Low

## REPORTES ESTADÍSTICOS

Data Rates	Sí
Ethernet Link Rate	Sí
Packet Errors	Sí
Up Time	Sí
Wireless Distance	Sí

## SISTEMA