

UAP-AC-IW

SKU 020916 · UAP-AC-IW



MARCA · UBIQUITI

UAP-AC-IW

Wall-mounted WiFi 5 AP with 4 spatial streams and a built-in 2-port switch ideal for seamless coverage of smaller rooms.

ESPECIFICACIONES TÉCNICAS

RESUMEN

Dimensiones	139.7 x 86.7 x 25.8 mm, (5.5 x 3.4 x 1")
Estándar WiFi	WiFi 5
Streams espaciales	4
Área de cobertura	25 m ² (270 ft ²)
Max. Client Count	250+
Uplink	GbE
Montaje	Wall, (Mount Incluido)
Método de alimentación	PoE, PoE+ (Required for PoE passthrough)

RENDIMIENTO

MIMO

5 GHz	2 x 2 (DL MU-MIMO)
2.4 GHz	2 x 2 (DL MU-MIMO)

TASA MÁX. DE DATOS

5 GHz	867 Mbps (BW80)
2.4 GHz	300 Mbps (BW40)

GANANCIA DE ANTENA

5 GHz	2 dBi
2.4 GHz	1 dBi

POTENCIA TX MÁX.

5 GHz	20 dBm
2.4 GHz	20 dBm
Max. BSSIDs	8 per Radio

TASAS DE DATOS SOPORTADAS

802.11ac (WiFi 5)	6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS23, HT 20/40)

FUNCIONES

Wireless Meshing	Sí
Band Steering	Sí
802.11v BSS Transition Management	Sí
802.11r Fast Roaming	Sí
802.11k Radio Resource Management (RRM)	Sí
Advanced Radio Management	Sí
Passpoint (Hotspot 2.0)	Sí
PORTAL CAUTIVO	
Custom Branding Landing Page	Sí
Voucher Authentication	Sí
Payment-Based Authentication	Sí
External Portal Server Support	Sí
Password Authentication	Sí
Guest Network Isolation	Sí
Private Pre-Shared Key (PPSK)	Sí
WiFi Speed Limiting	Sí
Client Device Isolation	Sí
WiFi Schedules	Sí
RADIUS over TLS (RadSec)	Sí
Dynamic RADIUS-assigned VLAN	Sí

HARDWARE