

F-POE-G2

SKU 021026 · F-POE-G2



MARCA · UBIQUITI

F-POE-G2

Connects remote PoE devices and provides data and power using fiber and DC cabling.

ESPECIFICACIONES TÉCNICAS

RESUMEN

Dimensiones	196.4 x 93.5 x 32.4 mm, (7.7 x 3.7 x 1.3")
Material de carcasa	Polycarbonat
Peso	288 g (10.2 oz)
Resistencia a intemperie	IPX5
Surge Protection	Built-in high-current gas discharge tube for DC terminal block and PoE port
Interfaz de red	(1) 1 Gbps SFP port, (1) DC terminal block, (1) DC RJ45 port DC injection, (1) GbE PoE port (10/100 MbE not supported)
Input DC voltage	16–57V
DC Output	Terminal block, 24V DC/50V DC, 2-wire
Método de alimentación	DC Terminal Block, 2-Wire, 24V DC/50 VDC, DC in RJ45 Port, 2-pair (4, 5+; 7, 8-) (24V DC input), or 4-pair (24V DC/50V DC input) passthrough, PoE RJ45 port, 2-pair (4, 5+; 7, 8-) (24V DC input), or 4-pair (24V DC/50V DC input) PoE passthrough
Power Consumption	1.5W (Typical)
ESD Protection	± 24kV Contact / Air for Ethernet
Temperatura de operación	-40 to 60° C (-40 to 140° F)
Humedad de operación	10 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC