

## IS-5AC

SKU 021028 · IS-5AC



MARCA · UBIQUITI

## IS-5AC

Compact, UISP-ready, 5 GHz WiFi bridge with enhanced surge protection and an interchangeable horn antenna.

## ESPECIFICACIONES TÉCNICAS

## MECÁNICA

Dimensiones	Without horn: , 131 x 131 x 65 mm (5.2 x 5.2 x 2.6"), With horn:, 174 x 174 x 150 mm (6.9 x 6.9 x 5.9")
Peso	Without horn: 408.2 g (0.9 lb), With horn: 725.7 g (1.6 lb)
Montaje	Pole Mount (incluido)
Wind Loading	36N at 200 km/h (8.09 lbf at 125 mph)
Wind Survivability	200 km/h (125 mph)

## HARDWARE

Interfaz de red	(1) GbE RJ45 port
Método de alimentación	Passive PoE 2-pair (4, 5+; 7, 8 return)
Fuente de poder	24V, 0.5A gigabit PoE adapter (incluido)
Rango de voltaje	20—27V DC
Consumo máximo	8.5W

## LEDS

Power	Sí
Temperatura de operación	-40 to 70 C (-40 to 158 F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC

## SOFTWARE

Operating Modes	Access Point, Station
-----------------	-----------------------

## FUNCIONES UBIQUITI ESPECÍFICAS

airMAX AC Mode	Sí
Discovery Protocol	Sí
Frequency Band Offset	Sí
Traffic Shaping with Burst Support	Sí
30/50/60 MHz Channels	Sí

## SERVICIOS

Bridging	Sí
DHCP	Sí
Ping Watchdog	Sí
Routing	Sí
SNMP	Sí
SSH	Sí
Webserver	Sí

## AJUSTE DE DISTANCIA

Dynamic Ack	Sí
QoS	WMM packet classification with user-level priority: High, Medium, Low

## REPORTES ESTADÍSTICOS

Data Rates	Sí
Ethernet Link Rate	Sí
Packet Errors	Sí
Up Time	Sí
Wireless Distance	Sí

## SISTEMA

Ganancia de antena	14 dBi
Antenna beamwidth	45° (Default Horn)