

LOCO5AC-5

SKU 021032 · Loco5AC



MARCA · UBIQUITI

Loco5AC

Compact, UISP-ready WiFi radio sporting a classic NanoStation design and an updated airMAX AC chipset.

ESPECIFICACIONES TÉCNICAS

MECÁNICA

Dimensiones	179 x 77.5 x 59.1 mm, (7.1 x 3.1 x 2.3")
Peso	180 g (6.4 oz)
Enclosure Materials	UV-stabilized polycarbonate
Montaje	Pole Mount (incluido)

HARDWARE

Interfaz de red	(1) GbE RJ45 port
Método de alimentación	Passive PoE 2-pair (4, 5+; 7, 8 return)
Fuente de poder	24V, 0.3A gigabit PoE supply (Not Incluido)
Rango de voltaje	22-27V DC
Consumo máximo	7W

LEDS

Signal Strength	Sí
Power	Sí
Ethernet	Sí
Temperatura de operación	-40 to 70° C (-40 to 158° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC, Anatel: 01405-19-08356

SOFTWARE

Operating Modes	Access Point, Station
-----------------	-----------------------

FUNCIONES UBIQUITI ESPECÍFICAS

airMAX AC Mode	Sí
Discovery Protocol	Sí
Frequency Band Offset	Sí
Traffic Shaping with Burst Support	Sí
30/50/60 MHz Channels	Sí

SERVICIOS

Bridging	Sí
DHCP	Sí
Ping Watchdog	Sí
Routing	Sí
SNMP	Sí
SSH	Sí
Webserver	Sí

AJUSTE DE DISTANCIA

Ackless Mode	Sí
Dynamic Ack	Sí
QoS	WMM packet classification with user-level priority: High, Medium, Low

REPORTES ESTADÍSTICOS

Data Rates	Sí
Ethernet Link Rate	Sí
Packet Errors	Sí
Up Time	Sí
Wireless Distance	Sí

SISTEMA