

ES-24-250W

SKU 021392 · Ubiquiti - Switch EdgeMAX Administrable de 24 Puerto...



MARCA · UBIQUITI

Ubiquiti - Switch EdgeMAX Administrable de 24 Puertos Giga...

Layer 2/3, PoE switch with (24) Gigabit RJ45 ports, (2) SFP ports, and a 250W power supply.

ESPECIFICACIONES TÉCNICAS

CARACTERÍSTICAS DESTACADAS

- (24) GbE RJ45 ports
- (2) SFP ports
- 250W total PoE availability
- Rack-mountable, 1U

MECÁNICA

Dimensiones	485 x 43.7 x 285.4 mm (19.1 x 1.7 x 11.2")
Peso	4.7 kg (10.4 lb)

HARDWARE

Interfaz de gestión	(1) RJ45 serial port, Ethernet In/Out-Band
Interfaz de red	(24) GbE RJ45 ports · (2) 1G SFP ports
PoE interface	(24) PoE/PoE+ 2-pair (Pins 1, 2+; 3, 6-) · (24) 24V DC passive PoE 2-pair (Pins 4, 5+; 7, 8-)
Rendimiento total sin bloqueo	26 Gbps
Switching capacity	52 Gbps
Forwarding rate	38.69 Mpps
Método de alimentación	100-240V AC, universal input, 50/60 Hz
Power supply	AC/DC, internal, 250W
Consumo máximo	30W (Excludes PoE output)
Total PoE available	250W
Max. PoE wattage per portby PSE	PoE+: 34.2W · Passive PoE: 17W
Voltage range PoE mode	PoE+: 50-57V · Passive PoE: 20-27V
Protección ESD/EMP	Air/contact: ±24 kV
LEDs	Ethernet ports: PoE, speed/link/activity · SFP ports: speed/link/activity
Botón	Factory reset
Rackmount	Yes, 1U
Shock and vibration	ETSI300-019-1.4 Standard
Temperatura de operación	-5 to 40° C (23 to 104° F)

HARDWARE (CONT.)

Humedad de operación	5 to 95% noncondensing
Certificaciones	CE, FCC, IC, Anatel: 01245-15-08356
Cumple NDAA	Yes