

ES-8-150W

SKU 021393 · Ubiquiti - Switch EdgeMAX Administrable de 8 Puertos...



MARCA · UBIQUITI

Ubiquiti - Switch EdgeMAX Administrable de 8 Puertos Gigab...

Gigabit switch with (8) RJ45 ports, (2) SFP ports, and a 150W power supply.

ESPECIFICACIONES TÉCNICAS

CARACTERÍSTICAS DESTACADAS

- (8) GbE RJ45 ports with 24V passive PoE
- (2) SFP ports
- 150W total PoE availability
- Desktop-mountable

MECÁNICA

Dimensiones	204 x 43 x 235 mm (8 x 1.7 x 9.3")
Peso	1.7 kg (3.8 lb)

HARDWARE

Interfaz de gestión	(1) RJ45 serial port, Ethernet In/Out-Band
Interfaz de red	(8) GbE RJ45 ports · (2) 1G SFP ports
PoE interface	(8) PoE/PoE+ 2-pair (Pins 1, 2+; 3, 6-) · (8) 24V/0.7A passive PoE 2-pair (Pins 4, 5+; 7, 8-)
Rendimiento total sin bloqueo	10 Gbps
Switching capacity	20 Gbps
Forwarding rate	14.88 Mpps
Método de alimentación	100-240V AC, universal input, 50/60 Hz, AC/DC integrated PSU · 42-56V DC terminal block, external input (Self-correcting polarity protection)
Power supply	AC/DC, internal, 150W DC
Consumo máximo	20W (Excludes PoE output)
Total PoE available	150W
Max. PoE wattage per port by PSE	PoE+: 34.2W · Passive PoE: 17W
Voltage range PoE mode	PoE+: 50-57V · Passive PoE: 20-27V
Protección ESD/EMP	Air/contact: ± 24kV
LEDs	System: status · Ethernet ports: PoE, link/speed/activity · SFP ports: link/speed/activity
Botón	Factory reset
Shock and vibration	ETSI300-019-1.4 Standard
Temperatura de operación	Internal AC/DC at 150W: -25 to 45° C (-13 to 113° F) · Internal AC/DC at 100W: -25 to 55° C (-13 to 131° F) · External DC: -25 to 60° C (-13 to 140° F)
Humedad de operación	5 to 95% noncondensing

HARDWARE (CONT.)