

Wave-Pico

SKU 021414 · Wave-Pico



MARCA · UBIQUITI

Wave-Pico

Lightweight, compact 60 GHz PtMP station powered by Wave Technology.

ESPECIFICACIONES TÉCNICAS

MECÁNICA

Dimensiones	Ø152.1 x 55.8 mm, (Ø6 x 2.2")
Peso	Without mount: 347 g (12.2 oz), With mount: 409 g (14.4 oz)
Material de carcasa	UV stabilized polycarbonate
Material de montaje	UV stabilized polycarbonate
Montaje	Pole Mount
Pole Mount Diameter	20 to 53.1 mm (0.8 to 2.1")
Wind Loading	31.3 N at 200 km/h (7 lbf at 125 mph)
Resistencia a intemperie	IPX6

HARDWARE

Procesador	Dual-core ARM® Cortex®-A53 at 1 GHz
Memoria	512 MB
Interfaz de red	(1) GbE RJ45 port
Consumo máximo	10W
Método de alimentación	Passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8 -), Passive PoE 2-pairs (4, 5+; 7, 8 -), for 44-54V DC only
Rango de voltaje	44-54V DC, 22-27V DC
Fuente de poder	48V DC, 0.5A gigabit PoE adapter (incluido)
Buttons	(1) Factory reset
LEDS	
Power	Flashing white: bootup in progress, White: not connected to UISP application, Blue: connected to UISP application, Flashing blue: locate in progress, Blue/white: firmware upgrade in progress
Ethernet	Flashing blue: Ethernet traffic detected
Link	White: 5 GHz link, Blue: 60 GHz link
Temperatura de operación	-40 to 60° C (-40 to 140° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	FCC, IC, CE

SOFTWARE