

USW-PRO-HD-24

SKU 021762 · USW-Pro-HD-24



MARCA · UBIQUITI

USW-Pro-HD-24

Professional-grade, Layer 3 Etherlighting™ switch with (2) 10 GbE, (22) 2.5 GbE, and (4) 10G SFP+ ports.

ESPECIFICACIONES TÉCNICAS

RESUMEN

Dimensiones 442 x 285 x 44 mm , (17.4 x 11.2 x 1.7")

DISPOSICIÓN DE PUERTOS

2.5 GbE RJ45	22, (2.5G/1G/100M/10M)
10 GbE RJ45	2, (10G/5G/2.5G/1G/100M)
10G SFP+	4, (10G/1G)
Redundancy	DC Power Backup
Layer 3	Sí
Formato	Rack mount (1U)
Etherlighting™	Sí

RENDIMIENTO

Capacidad de conmutación	230 Gbps
Rendimiento total no bloqueante	115 Gbps
Tasa de reenvío	171.12 Mpps
VLAN soportadas	1,000
Tamaño tabla MAC	32,000
IPv4 Static Routes	256
Packet Buffer Size	2 MB

LISTAS DE ACCESO

IPv4	128
MAC	128

FUNCIONES CAPA 3

DHCP Server (Local Networks)	Sí
DHCP Relay	Sí
Inter-VLAN Routing (Local Networks)	Sí
Static Routing (Local Networks)	Sí

FUNCIONES CAPA 2