

USW-Pro-Max-16-PoE

SKU 021872 · USW-Pro-Max-16-PoE



MARCA · UBIQUITI

USW-Pro-Max-16-PoE

A 16-port, Layer 3 Etherlighting™ switch with 2.5 GbE, PoE++ output, and versatile mounting options.

ESPECIFICACIONES TÉCNICAS

RESUMEN

Dimensiones **325.1 x 160 x 43.7 mm, (12.8 x 6.3 x 1.7")**

DISPOSICIÓN DE PUERTOS

1 GbE RJ45	12 (All PoE+), (1G/100M/10M)
2.5 GbE RJ45	4 (All PoE++), (2.5G/1G/100M/10M)
10G SFP+	2, (10G/1G)
Max. PoE Output	Up to PoE++
Total PoE Availability	180W
Layer 3	Sí
Formato	Rack mount (1U), desktop, wall
Etherlighting™	Sí

RENDIMIENTO

Capacidad de conmutación	84 Gbps
Rendimiento total no bloqueante	42 Gbps
Tasa de reenvío	62 Mpps
VLAN soportadas	1,000
Tamaño tabla MAC	16,000
IPv4 Static Routes	256
Packet Buffer Size	1.5 MB

LISTAS DE ACCESO

IPv4	128
MAC	128

FUNCIONES CAPA 3

DHCP Server (Local Networks)	Sí
DHCP Relay	Sí
Inter-VLAN Routing (Local Networks)	Sí
Static Routing (Local Networks)	Sí

FUNCIONES CAPA 2