

Wave-AP-Gen2

SKU 021875 · Wave-AP-Gen2



MARCA · UBIQUITI

Wave-AP-Gen2

60 GHz + 5 GHz multipoint base station featuring 90-degree sectoral coverage, 31-client capacity, 2.7 Gbps symmetrical speed, and antenna connectors for 5 GHz range extension.

ESPECIFICACIONES TÉCNICAS

MECÁNICA

Dimensiones	158.3 x 286.8 x 100.2 mm, (6.2 x 11.3 x 3.9")
Peso	1.5 kg (3.3 lb)
Material de carcasa	UV stabilized polycarbonate, aluminum alloy
Pole Mount Diameter	25.4 to 60 mm (1 to 2.4")
Wind Loading	109.8 N at 200 km/h (25 lbf at 125 mph)
Resistencia a intemperie	IPX6

HARDWARE

Procesador	Quad-core ARM® Cortex®-A53 at 1.4 GHz
Memoria	512 MB
Interfaz de red	(1) 2.5 GbE RJ45 port, (1) 10G SFP+ port
Consumo máximo	24W
Método de alimentación	Passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-), Passive PoE 2-pairs (4, 5+; 7, 8-), for 44-54V DC only
Rango de voltaje	44-54V DC, 22-27V DC
Fuente de poder	48V DC, 0.65A 2.5 GbE PoE adapter (incluido)
GPS	Sí
Buttons	(1) Factory reset
LEDS	
Power	Flashing white: bootup in progress, White: not connected to UISP application, Blue: connected to UISP application, Flashing blue: locate in progress, Blue/white: firmware upgrade in progress
Ethernet	Flashing white: Ethernet traffic detected, Flashing blue: SFP+ traffic detected
GPS	Blue: receiving at least (4) GPS satellite signal
Temperatura de operación	-40 to 60° C (-40 to 140° F)
Humedad de operación	5 to 95%, no condensada
Cumple NDAA	Sí
Certificaciones	FCC, IC, CE

SOFTWARE