

## UVC-G4 Doorbell Pro PoE Kit

SKU 090222 · UVC-G4 Doorbell Pro PoE Kit



MARCA · UBIQUITI

## UVC-G4 Doorbell Pro PoE Kit

Premium UniFi doorbell with integrated PoE and included PoE chime for plug-and-play installation.

## ESPECIFICACIONES TÉCNICAS

## RESUMEN

Dimensiones	Device: 160.6 x 51.7 x 35.1 mm (6.3 x 2 x 1.4"), Pared: 159.3 x 50.3 x 17.5 mm (6.3 x 1.9 x 0.7"), Wedge: 161.1 x 52.1 x 25.7 mm (6.3 x 2.1 x 1"), On-wall mount: 161.1 x 52.1 x 25.75 mm (6.3 x 2.1 x 1")
Visión nocturna IR	6 m (20 ft)
Detección inteligente (personas, vehículos, animales)	Sí
Resolución	FHD
Campo de visión	Main camera: H: 138°, V: 114°, D: 155° (LDC On), Main camera: H: 160°, V: 117°, D: 160° (LDC Off), Package camera: H: 97.5°, V: 79.4°, D: 118.2°
Audio	Two-way audio
Resistencia a intemperie	IPX4
Montaje	Wall, wedge (incluido), Gang box, junction box (opcional)
NFC Card & Keyfob Access	Sí
Two-Way Intercom & Doorbell Access	Sí

## RENDIMIENTO

Interfaz de red	GbE RJ45 port
VIDEO	
Cuadros por segundo (máx.)	30 FPS
Resolución	Main camera: 2MP 1600 x 1200 (4:3), Package camera: 2MP 1600 x 1200 (4:3)
ÓPTICA	
Sensor	Main camera: 5MP CMOS, Package camera: 8MP CMOS
Lente	Fixed focal length
Modo nocturno	Built-in IR LED illumination and IR cut filter
HARDWARE	
Consumo máximo	7W
Rango de voltaje	37—57V DC
Método de alimentación	PoE
Procesador	Quad-core Arm® Cortex®-A53 based chip
Peso	Device: 264 g (9.3 oz), Pared: 56 g (2 oz), Wedge: 33 g (1.2 oz), On-wall mount: 53 g (1.9 oz)
Material de carcasa	Polycarbonate, aluminum alloy
Material de montaje	Flat wall mount: aluminum alloy, 20° wedge mount: polycarbonate
Botón	(1) Ring button, (1) Factory reset
Temperatura de operación	-30 to 40° C (-22 to 104° F)
Humedad de operación	0 to 90%, no condensada
Cumple NDAA	Sí
Certificaciones	CE, FCC, IC, SRRC
SOFTWARE	
Mobile app	UniFi Protect iOS™ and Android™