

N-SW

SKU 020273 · Ubiquiti - NanoSwitch No Administrable de 4 Puertos ...



MARCA · UBIQUITI

Ubiquiti - NanoSwitch No Administrable de 4 Puertos Gigabi...

An outdoor, 4-port Gigabit switch with up to 4 Gbps total, non-blocking line rate support.

ESPECIFICACIONES TÉCNICAS

CARACTERÍSTICAS DESTACADAS

- (3) GbE RJ45 ports with 24V passive PoE
- 24W PoE supply
- Outdoor, weather-resistant enclosure

MECÁNICA

| | |
|--------------------|--------------------------------------|
| Dimensiones | 196 x 93 x 32 mm (7.7 x 3.7 x 1.3") |
| Peso | 269 g (9.5 oz) |
| Enclosure material | White polycarbonate |

HARDWARE

| | |
|-----------------------------------|--|
| Interfaz de red | (4) GbE RJ45 ports [(1) PoE-in, (3) PoE passthrough] |
| Total non-blocking line rate | 4 Gbps |
| Método de alimentación | Passive 24V, 2-pair PoE-in |
| Rango de voltaje soportado | 21.6-30V |
| Consumo eléctrico | Typical: 1.5W · Max.: 30W |
| Power supply | POE-24-30W-G PoE adapter (Not included) |
| Protección ESD/EMP | Air/contact: ± 24 kV |
| Passive PoE Max. Wattage per port | 24V, 2-pair, 1A per port (24W) |
| Total passive PoE Max. Wattaget | 24V, 2-pair, 1A for 3 ports (30W) |
| LEDs | Speed/Link/Activity (All ports) |
| Temperatura de operación | -30 to 70° C (-22 to 158° F) |
| Humedad de operación | 5 to 95% noncondensing |
| Cumple NDAA | Yes |