

DH-PFM302

DC12V2A Power Adapter



- Inverted bucket water-proof design.
- Wall mount installation.
- Offers enough space to accommodate cables and joints.
- Shell flame resistance V-0 level.

Technical Specification

Function

Input Voltage	180–240 VAC
Output Voltage	12 VDC
Rated Output Current	2 A
Rated Power	24 W
Power Consumption In Idle	≤0.3 W
Efficiency	≥82.09%

Port

Input Port	2 pin wire terminal
Output Plug	Φ5.5 mm × Φ2.1 mm × 11.0 mm (0.22" × 0.08" × 0.43") (OD × ID × L)

Protection

Protection	Protects against overcurrent, overvoltage, overheating, short circuits and abnormal input.
Surge Protection Grade	Common mode: ±4 kV Differentiate mode: ±2 kV
Statics Protection	Air discharge: ±8 kV Contact discharge: ±4 kV

Structure

Installation	Wall mount
Product Dimensions	128.5 mm × 75.3 mm × 34.0 mm (5.06" × 2.96" × 1.34")
Appearance Color	Gray
Net Weight	0.14 kg (0.31 lb)
Gross Weight	0.17 kg (0.37 lb)
Packaging Dimensions	131.0 mm × 76.0 mm × 35.0 mm (5.16" × 2.99" × 1.38")
Output Cable Length	60 mm (2.36")

Environment

Operating Temperature	−5 °C to +40 °C (+23 °F to +104 °F)
Operating Humidity	10%–90% (RH)
Storage Temperature	−30 °C to +80 °C (−22 °F to +176 °F)
Storage Humidity	10%–90% (RH)

Ordering Information

Type	Model	Description
Power Adapter	DH-PFM302	Power Adapter

Dimensions (mm[inch])

