

DHI-ASA2212GL-MEW

Dahua Card Swiping, Password, Fingerprint Attendance Standalone



Series Overview

Time Attendance Terminal is a unique device that specializes in attendance management. It not only supports multiple authentication methods, but also features basic access control functions. This system can be used as a standalone device for attendance and is also compatible with various platforms.

Scene

Widely used in multiple scenes such as office buildings, schools, compound buildings, communities, factories, public venue, commercial centers, government buildings, and more.

Technical Specification

System

Main Processor	Embedded Processor
Button Type	Mechanical
Network Protocol	IPv4;UDP;P2P;IPv6;TCP
OSDP Protocol	Yes
Input Method	T9
Interoperability	ONVIF;CGI
SDK	Yes
API	Yes

Basic

Display Screen	2.4-inch display screen
Product Type	Attendance Standalone
Screen Type	Non-touchscreen

- Built of PC and ABS material, and comes with 2.4" LCD with a resolution of 240 (H) × 320 (V).
- Built-in rechargeable lithium battery, which can be used for about 3 hours after being fully charged.
- Convenient to configure through its webpage that is accessible to both computers and mobile devices.
- Attendance can be marked through card(IC,ID), password and fingerprint.
- Supports 3,000 users, 3,000 cards, 3,000 fingerprints, and 100,000 attendance records.
- Supports configuring up to 20 departments, and 24 shifts directly on the device. Each shift can contain 2 working periods, and 1 overtime period.
- Features voice prompts.
- Supports importing and exporting information on people, cards, shifts, and schedules through the USB flash drive.
- Supports TCP/IP connection, auto registration, P2P registration and DHCP.
- Online update and update through USB.

Screen Resolution	240 (H) × 320 (V)
Voice Prompt	Yes
Powering On/Off Button	1
Casing Material	PC + ABS

RFID

Card Type	IC card;ID card
Modulation Type	ASK
Frequency Range	13.56 MHz;125 kHz
Max. Transmission Power	13.56MHz : 42dBuA/m @10m;125 kHz : 66dBuA/m @10m

Function

Period List	128 periods
Holiday Period	128 periods
Network Update	Yes
Restricted List/Trusted List	Yes
Auto Registration	Yes

Network

Max. Transmission Power	≤20dBm@2400-2483.5MHz
Wi-Fi	Yes
Wireless Standard	IEEE802.11b/802.11g/802.11n

Time Attendance Terminal | DHI-ASA2212GL-MEW

Wireless Frequency Range	2400-2483.5MHz
Performance	
Response Time	0.2 S
Card Reading Distance	3 cm (1.18")
Fingerprint Sensor Type	Optical
Fingerprint Verification Mode	1:N
Fingerprint Comparison Time	1.5 S
Fingerprint Recognition Time	0.5 S
Attendance	
Export Attendance Record	USB flash drive export
Attendance Check Mode	Auto/Manual Mode;Auto Mode;Manual Mode;Fixed Mode
Attendance Statistics	Yes
Department Setting	20 departments
Schedule Setting	24 shifts
Ring Tone	Yes
User	
User (Card) Type	General user, VIP user, patrol user, guest user, blocklist user, other users, custom user 1 and custom user 2
Capacity	
User Capacity	3,000
Fingerprint Capacity	3,000
Card Capacity	3,000
Password Capacity	3,000
Record Capacity	100,000
Port	
USB	1 × USB 2.0 port
Network Port	1 × RJ-45 10/100 Mbps self-adaptive Ethernet port
Exit Button	1 channel
Door Status Detection	1 channel
Lock Control	1 channel
Alarm	
Duress Alarm	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
General	
Power Adapter	Included
Power Supply	12 VDC, 1 A; Lithium battery

Power Consumption	≤6 W
Product Dimensions	181.6 mm × 135.6 mm × 32.7 mm (7.15" × 5.34" × 1.29") (L × W × H)
Packaging Dimensions	298 mm × 162 mm × 71 mm (11.73" × 6.38" × 2.8") (L × W × H) (Single device in inner box) 383 mm × 313 mm × 349 mm (15.08" × 12.32" × 13.74") (L × W × H) (Protective case)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5%–95% (RH), non-condensing
Operating Environment	Indoor
Gross Weight	0.61 kg (1.34 lb)
Installation	Surface Mount
Certifications	CE
Storage Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Storage Humidity	30%–75% (RH), non-condensing

Ordering Information

Type	Model	Description
Attendance Standalone	DHI-ASA2212GL-MEW	Dahua Card Swiping, Password, Fingerprint Attendance Standalone

Installation

Dimensions (mm[inch])

