

IPMECD-0161-M2020

Barrier Rod



- 3 to 4 m telescopic folding arm that can be used on either side of the boom gate. (The lengths of the main pole and auxiliary pole can be adjusted from 1.5 meters to 2 meters.)
- Made of aluminum alloy, and designed with an anti-rust case that was treated with electrostatic spray.
- Elastic anti-smashing rubber strip at the bottom.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic

Color	Red and white
Matched Product	DHI-IPMECD-1061 Series Barrier

General

Operating Temperature	-30 °C to +65 °C (-22 °F to +149 °F)
Storage Temperature	-30 °C to +65 °C (-22 °F to +149 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (Aluminum)
Product Dimensions	3,030.0 mm × 130.0 mm × 45.0 mm (119.29" × 5.12" × 1.77") (L × W × H)
Packaging Dimensions	3,200.0 mm × 180.0 mm × 100.0 mm (126.00" × 7.09" × 3.94") (L × W × H)
Net Weight	5.0 kg (11.02 lb)
Gross Weight	5.4 kg (11.90 lb)
Installation	Compatible with barrier installation
Anti-corrosion Level	Basic Protection

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-0161-M2020	Barrier Rod

Dimensions (mm[inch])

